

Chip Resistor ACCH Series

**Automotive
AEC-Q200**

RoHS Compliant
Halogen Free
REACH Compliant



High
Power

Thick Film

Low
Resistance

Part Numbering


A	CCH	00	1206	-	R100	F	TP
Grade	Product Series	Control Code	Dimensions Code (inch)	Special Code	Nominal Resistance	Tolerance	Taping Code
			0402 1.0x0.5x0.35		0.1Ω R100	F ±1%	TH (10000PCS) : 0402
			0603 1.6x0.8x0.45		0.33Ω R330	J ±5%	TP (5000PCS) : 0603-1210
			0805 2.0x1.25x0.5		0.56Ω R560		TE (4000PCS) : 2010-2512
			1206 3.05x1.55x0.5				
			1210 3.05x2.55x0.55				
			2010 4.95x2.45x0.7				
			2512 6.4x3.2x0.7				

Chip Resistor ACCH Series

**Automotive
AEC-Q200**


ACCH Type

■ Dimensions




unit:mm

■ Recommended Land Pattern



unit:mm

■ Measurement Point



⊕ Current Terminal
⊖ Voltage Terminal

unit:mm

Type	Dimensions					Recommended Land Pattern			Measurement Point	
	L	W	H	L1	L2	A	B	C	A ±0.05	B ±0.05
ACCH000402	1.00±0.10	0.50±0.10	0.35±0.10	0.25±0.10	0.20±0.15	0.5	1.5	0.6	0.8	0.24
ACCH000603	1.60±0.10	0.80±0.10	0.45±0.10	0.25±0.15	0.35±0.15	0.8	2.1	0.9	1.35	0.35
ACCH000805	2.00±0.10	1.25±0.10	0.50±0.10	0.35±0.20	0.35±0.20	1.2	3.0	1.3	1.8	0.35
ACCH001206	3.05±0.10	1.55±0.10	0.50±0.10	0.45±0.20	0.65±0.25	2.2	4.2	1.6	2.9	0.35
ACCH001210	3.05±0.10	2.55±0.10	0.55±0.10	0.50±0.20	0.50±0.20	2.2	4.2	2.8	2.9	0.35
ACCH002010	4.95±0.10	2.45±0.10	0.70±0.10	0.65±0.20	0.70±0.20	3.5	6.1	2.8	4.5	1.15
ACCH002512	6.40±0.20	3.20±0.20	0.70±0.10	0.72±0.20	0.69±0.20	3.8	8.0	3.5	5.9	1.60

Electrical Characteristics Resistance Range:

Type	Rated Power at 70°C (W)	Rated Current (A) Max.	Overload Current (A) Max.	T.C.R (ppm/°C)	Resistance Range (mΩ)
					±1%, ±5% E-24 · E-96
ACCH000402	1/10	1.82	4.56	±1500	30 ≤ R < 37
				±1200	37 ≤ R < 60
				±600	60 ≤ R < 100
				±500	100 ≤ R < 400
				±300	400 ≤ R < 1000
ACCH000603	1/4	2.88	7.21	±1500	30 ≤ R < 37
				±1200	37 ≤ R < 60
				±600	60 ≤ R < 100
				±200	100 ≤ R < 1000
ACCH000805	2/5	4.47	11.18	±1200	20 ≤ R < 33
				±800	33 ≤ R < 50
				±600	50 ≤ R < 100
				±300	100 ≤ R < 1000
Operating Temperature Range				-55°C ~ +155°C	



Chip Resistor ACCH Series

**Automotive
AEC-Q200**

Electrical Characteristics Resistance Range:

Type	Rated Power at 70°C (W)	Rated Current (A) Max.	Overload Current (A) Max.	T.C.R (ppm/°C)	Resistance Range (mΩ)
					±1%, ±5% E-24 · E-96
ACCH001206	1/2	5	12.5	±1200	20 ≤ R < 25
				±1000	25 ≤ R < 50
				±600	50 ≤ R < 100
				±300	100 ≤ R < 1000
ACCH001210	3/4	6.12	15.31	±1000	20 ≤ R < 25
				±700	25 ≤ R < 50
				±400	50 ≤ R < 100
				±300	100 ≤ R < 1000
ACCH002010	1	7.07	17.67	±1200	20 ≤ R < 25
				±700	25 ≤ R < 50
				±500	50 ≤ R < 100
				±300	100 ≤ R < 1000
ACCH002512	2	10	25	±1000	20 ≤ R < 25
				±700	25 ≤ R < 50
				±500	50 ≤ R < 100
				±300	100 ≤ R < 1000
Operating Temperature Range				-55°C ~ +155°C	

Legal disclaimer

CHILISIN, its distributors and agents (collectively, "CHILISIN"), hereby disclaims any and all liabilities for any errors, inaccuracies or incompleteness contained in any product related information, including but not limited to product specifications, datasheets, pictures and/or graphics. CHILISIN may make changes, modifications and/or improvements to product related information at any time and without notice.

CHILISIN makes no representation, warranty, and/or guarantee about the fitness of its products for any particular purpose or the continuing production of any of its products. To the maximum extent permitted by law, CHILISIN disclaims (i) any and all liability arising out of the application or use of any CHILISIN product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for a particular purpose, non-infringement and merchantability.

CHILISIN defined this product is for general electrical use , not design for any application for automotive electrical ,life-saving or life support equipment, or any application which may inflict casualties if CHILISIN product failure occurred. When consumer is using or selling products of CHILISIN without having discussion with the sales representatives and specifically stated the applicability mentioned above in a written form, then the client need to take a full responsibility and agree to protect CHILISIN from punishment and damage.

Information provided here is intended to indicate product specifications only. CHILISIN reserves all the rights for revising this content without further notification, as long as products are unchanged. Any product change will be announced by ECN.