




1.Features

1. High common mode impedance at high frequency effects excellent noise suppression performance.
2. DVI2012F2SF series realizes small size and low profile. 2.0x1.2x1.2 mm.
3. 100% Lead(Pb) & Halogen-Free and RoHS compliant.




2.Dimension



當破損面積 < 5%, 產品列入允收品範圍

產品破損寬度



Series	A(mm)	B(mm)	C(mm)	D1(mm)	D2(mm)	E(mm)
2012F2SF	2.0±0.2	1.2±0.2	1.2±0.2	0.50±0.1	0.51±0.1	0.15±0.1

3.Part Numbering



- A: Series
- B: Dimension
- C: Material Ferrite Core
- D: Number of Lines 2=2 lines
- E: Type S=Shielded , N=Unshielded
- F: Lead free
- G: Impedance 500=50Ω
- H: Packaging T=Taping and Reel
- I: Rated Current 04=400mA

4.Specification

TAI-TECH Part Number	Common mode Impedance (Ω)		Test Frequency (MHz)	DC Resistance (Ω) max.	Rated Current (mA)	Rated Volt. (Vdc)	Withstand Volt. (Vdc)	IR (Ω) min.
	50 typ.	38 min.						
DVI2012F2SF-500T04	50 typ.	38 min.	100	0.30	400	50	125	10M
DVI2012F2SF-900T04	90 typ.	65 min.	100	0.30	400	50	125	10M

