


DS Radial Type, Standard Series


- Endurance : 2.5V 70°C 1000 hours, 2.7V 65°C 1000 hours, 3.0V 65°C 1000 hours
- The small size and high capacitance, low resistance
- Can be charge and discharge more times than secondary batteries



Item	Characteristics		
Operating temperature range	-30 ~ +70°C	-40 ~ +65°C	-40 ~ +65°C
Rated Voltage	2.5 VDC	2.7 VDC	3.0 VDC
Capacitance tolerance	0 ~ +20% at 20°C		
Temperature characteristics	Capacitance change	Within $\pm 5\%$ of initial value at +20°C	
	Internal resistance change	Within 50% of initial value at +20°C	
Endurance (2.5V:70°C, 2.7V:65°C, 3.0V:65°C)	Test time	1000 hours	
	Capacitance change	Within $\pm 30\%$ of specified value	
	Internal resistance change	Less than 100% of specified value	
Shelf life(2.5V:70°C, 2.7V:65°C, 3.0V:65°C)	After 1000 hours no load test same as endurance		
Life Time at RT ⁽¹⁾	10 years	(1) $ \Delta C < 30\%$ and $\Delta ESR < 100\%$ of specified value, respectively and $LC <$ specified value	
Cycle Life (25°C) ⁽¹⁾⁽²⁾	500,000 cycles	(2) Cycle : between rated voltage and half rated voltage under constant current at 25°C	

DRAWING

Unit : mm



ØD	8	10	16	18
P	3.5	5.0	7.5	7.5
Ød	0.6	0.6	0.8	0.8
β	1.5		2.0	

CHARACTERISTIC LIST & DIMENSIONS

Rated Voltage	Capacitance (F)	ESR, 1KHz (mΩ)	ESR, DC (mΩ)	LC (72hr) (mA Max.)	Specific Energy		Specific Power		Weight (g)	Volume (ml)	Dimension ØD×L(mm)
					(Wh/kg)	(Wh/L)	(W/kg)	(W/L)			
2.5	3	140	350	0.008	1.63	2.60	1,339	2,143	1.60	1.0	8 × 20
	5	110	250	0.013	1.97	2.71	1,364	1,875	2.2	1.6	10 × 20
	10	65	120	0.025	2.48	3.62	1,786	2,604	3.5	2.4	10 × 30
	25	35	65	0.063	2.89	4.34	1,538	2,308	7.5	5.0	16 × 25
	60	20	30	0.150	3.77	5.11	1,812	2,451	13.8	10.2	18 × 40
2.7	3	60	90	0.008	2.17	3.04	6,943	9,720	1.4	1.0	8 × 20
	5	50	70	0.014	2.41	3.16	5,951	7,811	2.1	1.6	10 × 20
	10	30	50	0.027	3.49	4.22	6,033	7,290	2.9	2.4	10 × 30
	25	20	35	0.068	3.78	5.06	3,730	4,999	6.7	5.0	16 × 25
	50	10	20	0.140	4.40	4.96	3,803	4,288	11.5	10.2	18 × 40
3.0	3	60	105	0.009	2.34	3.75	6,429	10,286	1.6	1.0	8 × 20
	5	50	90	0.015	2.84	3.91	5,455	7,500	2.2	1.6	10 × 20
	10	30	45	0.030	3.57	5.21	6,857	10,000	3.5	2.4	10 × 30
	25	20	30	0.075	4.17	6.25	4,800	7,200	7.5	5.0	16 × 25
	60	10	20	0.180	5.43	7.35	3,913	5,294	13.8	10.2	18 × 40