



em eco|mate® Family Overview

The **ecomate® Family** of circular, multiway connectors provide an IP65-69k rating range (in mated condition) for indoor / outdoor industrial applications and feature robust, durable plastic or metal designs with either circular bayonet or rapid coupling systems. With a current rating range of 5 to 300A across the individual series, our ecomate® Family of products is perfect for a wide range of Factory Automation, Industrial, Heavy Equipment, Heavy Duty, Transportation, and Entertainment/Lighting markets.

ecomate® RM is available in an **ecomate® RSSM (Superior Seal) IP69K** option. **ecomate® RM** is also available in an **ecomate® RM High Amp** option, featuring **RADSOK®** Contact technology.







em eco|mate® C16

em eco|mate® RM

em eco|mate® AQUARIUS™

em eco|mate® Plastic

IP Rating		 	
Shell Sizes / Inserts	3 Shell Sizes / 11 Inserts	8 Shell Sizes / 33 Inserts (Includes RSSM and High Amp)	6 Shell Sizes / 28 Inserts
Approvals	VDE, UL and CSA	Pending UL ECBT2 & ECBT8	UL ECBT2
Materials	Thermoplastic UL94 V-0	Body-Zinc Alloy; Coupling-Nickel Alum.	Thermoplastic UL94 V-0
Contacts	Stamped & Formed	Machined, Stamped & Formed, PCB (ecomate® RM (Rugged Metal) contacts are fully compatible with ecomate® Aquarius™ contacts, providing significantly increased product flexibility.)	S&F, Machined, Solder
Termination	Screw (Field Install), Crimp	Crimp, Solder	Screw (Field Install), Crimp, Solder
Coupling System	Circular Bayonet		Rapid Threading
Amperage	Up to 50A/900V	Up to 45A/500V (RADSOK® 86 to 300A)	10 to 20A
Operating Temp	-40°C to +125°C	-40°C to +115°C	-40°C to +125°C

em eco|mate® Family



Standard products. Custom solutions
Customer Service +1 800 394 7732

ecomate® RM/RSSM - 8 Shell Sizes/28 Insert Arrangements (For reference only)

Size 10 3 Pos 13A/500V	Size 10 4 Pos 13A/300V	Size 10 4 Pos 13A/350V	Size 10 6 Pos 5A, 7A/150V	Size 10 6 (3+3) Pos 13A, 5A/500V	Size 12 3 Pos 13A/300V	Size 12 4(2+2) Pos 23A, 7.5A/350V	Size 12 4(2+2) Pos 23A, 13A/500V	Size 12 8 Pos 13A/300V
Size 12 10 Pos 5A, 7.5A/150V	Size 14 3 Pos 45A/600V	Size 14 4 Pos 23A/350V	Size 14 4 Pos 23A, 13A/350V	Size 14 7 Pos 13A/500V	Size 14 8 Pos 13A/300V	Size 14 12 Pos 13A/300V	Size 14 19 Pos 5A, 7.5A/150V	Size 16 4 Pos 45A/500V
Size 16 9 Pos 23A, 13A/250V	Size 16 19 Pos 13A/300V	Size 16 26 Pos 5A, 7.5A/150V	Size 18 8 Pos 23A/375V	Size 18 23 Pos 13A/300V	Size 18 32 Pos 5A, 7.5A/150V	Size 20 28 Pos 13A/300V	Size 22 35 Pos 13A/300V	Size 22 38 Pos 13A/300V
Size 24 48 Pos 13A/300V								

ecomate® RM High Amp (Includes RADSOK® Contact Technology) - 4 Shell Sizes/5 Insert Arrangements (For reference only)

Size 10 1 Pos 86A/630V	Size 14 1 Pos 120A/630V	Size 16 1 Pos 120A-180A/630V	Size 20 1 Pos 120A-300A/630V	Size 20 3 Pos 86A/630V



ecomate® Aquarius™ - 6 Shell Sizes/28 Insert Arrangements (For reference only)

Size 8	Size 8	Size 10	Size 10	Size 10	Size 10	Size 10	Size 12	Size 12
3 Pos 7A/250V	4 Pos 7A/250V	3 Pos 13A/500V	4 Pos 13A/500V	4 Pos 13A, 7.5A/500V	6 Pos 5A, 7A/250V	Size 10 6 (3+3) Pos 13A, 5A/500V	3 Pos 13A/600V	4(2+2) Pos 13A/500V
Size 12	Size 12	Size 12	Size 14	Size 14	Size 14	Size 14	Size 14	Size 14
8 Pos 13A 500V	4(2+2) Pos 23A, 7.5A/350V	10 Pos 5A, 7.5A/250V	3 Pos 45A/600V	7 Pos 13A/500V	8 Pos 13A/500V	12 Pos 13A/500V	4 Pos 23A, 13A/500V	4 Pos 23A/500V
Size 14	Size 16	Size 16	Size 16	Size 16	Size 18	Size 18	Size 18	Size 18
19 Pos 5A, 7.5A/250V	4 Pos 45A/500V	19 Pos 13A/500V	9 Pos 23A & 13A/350V	26 Pos 5A, 7.5A/250V	23 Pos 13A/500V	8 Pos 23A/500V	32 Pos 5A, 7.5A/250V	13 Pos (10)#16(Ø1.6), 13A, 500V (3)Coax RG316/U, 1A, 500V
Size 18								
8 Pos RJ45 1.5A, 125V								

ecomate® C16 - 3 Shell Sizes/11 Insert Arrangements (For reference only)

Size 1	Size 1	Size 1	Size 1	Size 1	Size 1	Size 2	Size 2	Size 2
2+PE Pos 36A/750V	3+PE Pos 23A/900V	8+PE Pos 10A, 12A/400V	12+3+PE Pos 12A, 6A/320V	14+PE Pos 16A, 6A/100V	17+PE Pos 5A, 6A/100V, 250V	5+PE Pos 16A, 21A/400V	12+PE Pos 21A, 11A/300V	14+PE Pos 6A, 12A/400V

Size 2	Size L
19+PE Pos 5A, 6A/250V	4+PE Pos 36A/600V

ecomate® Plastic - 1 Shell Size/4 Insert Arrangements (For reference only)

3+PE Pos 16A/400V Standard	3+PE Pos 14A/600V High Voltage	6+PE Pos 13A/250V Standard	6+PE Pos 14A/600V High Voltage

Available  **ecomate® Plastic** Assembled Solutions



Example PN:
CA0162C22302012



Example PN:
CA0161G113003

For more information, contact: Customer Service, +1 800 394 7732, csr@amphenol-sine.com

© 2019 Amphenol Sine Systems Corporation, 44274 Morley Drive, Clinton Township MI 48036 USA. www.amphenol-sine.com. Customer Service +1 800 394 7732
Every effort has been made to ensure that the information contained in this document is accurate at the time of publication. Specifications or information stated in this document are subject to change without notice.